


NT H.R.C Low Voltage Fush and Base


APPLICATION

NT type low voltage H.R.C. fuse features light in weigh, small in size, low in power, loss and high in beaking capacity. This product has been widely used in overload and short circuit protection of electric installations.


This product conforms to IEC269 and VDE0636 standards of the rating at the world advanced level.




NT00C



NT00



NT0



NT1

SPECIFICATIONS

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss (W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT00C NT00	2	500, 600	0.41	0.15	sist 101	160	0.2
	4		0.81				
	6		0.62				
	10		1.08				
	16		1.60				
	20		1.81				
	25		2.31				
	32		3.07				
	36		3.17				
	40		4.05				
NT0	50	500, 600	4.25	0.2	sist 101	160	0.32
	63		5.7				
	80		7				
	100		10.3				
	6		4.70				
	10		1.42				
	16		2.45				
	20		2.36				
	35		2.7				
	32		3.74				
NT0	35	500, 600	4.3	0.2	sist 101	160	0.32
	40		4.7				
	50		5.5				
	63		6.9				
	80		7.6				
	100		8.9				
	125		10.1				
160	15.2						

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss (W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT1	80	500, 600	6.2	0.36	sist 201	250	0.8
	100		7.5				
	125		10.2				
	160		13				
	200		15.2				
	224		16.8				
	250		18.3				