

Drop-out Fuse Cutout



FSC-1

12kV~15kV

Type	Rated voltage (kV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-1	15	100	10000	110	40	250	7.3	38.5 x 34.5 x 10.5
FSC-1	15	200	12000	110	40	250	7.3	



FSC-7

12kV~15kV

Type	Rated voltage (kV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-7	11	100	6000	110	42	340	7.5	49 x 27 x 11.5
FSC-7	11	200	8000	110	42	340	7.5	



FSC-18

24kV~27kV

Type	Rated voltage (kV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-18	24	100	8000	150	65	530	12	48 x 34.5 x 14
FSC-18	24	200	10000	150	65	530	12	



FSC-22

33kV~36kV

Type	Rated voltage (kV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-22	33	100	10000	170	70	720	15.5	57 x 38 x 14.5
FSC-22	33	200	20000	170	70	720	15.5	