

Heat Shrinkable Tubing

FUNCTION

1. Wire coat and insulation.
2. Make the joint of terminal block and wire insulated.
3. Divide the colors.
4. Water-proof.
5. Protection and insulation of insitors and electrical capacitors.

SPECIFICATIONS

Clor: Black, white, red, blue, yellow, green, brown, grey, orange and purple.

Type	AS supplied		AS supplied		Packing (m/roll)
	I. D (mm)	Thickness	I. D (mm)	Thickness	
DRS-1	1.0	0.2 ± 0.05	0.5	0.4 ± 0.05	400
DRS-1.5	1.5	0.2 ± 0.05	0.75	0.4 ± 0.05	300
DRS-2	2.0	0.25 ± 0.05	1.0	0.45 ± 0.1	200
DRS-2.5	2.5	0.25 ± 0.05	1.25	0.45 ± 0.1	
DRS-3	3.0	0.25 ± 0.05	1.5	0.45 ± 0.1	100
DRS-3.5	3.5	0.25 ± 0.05	1.75	0.45 ± 0.1	
DRS-4	4.0	0.25 ± 0.05	2.0	0.45 ± 0.1	
DRS-5	5.0	0.35 ± 0.05	2.5	0.55 ± 0.1	
DRS-6	6.0	0.35 ± 0.05	3.0	0.55 ± 0.1	
DRS-7	7.0	0.35 ± 0.05	3.5	0.55 ± 0.1	
DRS-8	8.0	0.35 ± 0.05	4.0	0.55 ± 0.1	
DRS-9	9.0	0.35 ± 0.05	4.5	0.55 ± 0.1	
DRS-10	10.0	0.35 ± 0.05	5.0	0.60 ± 0.1	
DRS-11	11.0	0.35 ± 0.05	5.5	0.60 ± 0.1	
DRS-12	12.0	0.35 ± 0.05	6.0	0.70 ± 0.1	100
DRS-13	13.0	0.35 ± 0.1	6.5	0.4 ± 0.05	
DRS-14	14.0	0.35 ± 0.1	7.0	0.4 ± 0.05	
DRS-15	15.0	0.35 ± 0.1	7.5	0.4 ± 0.05	
DRS-16	16.0	0.35 ± 0.1	8.0	0.4 ± 0.05	
DRS-17	17.0	0.35 ± 0.1	8.5	0.4 ± 0.05	50
DRS-18	18.0	0.4 ± 0.1	9.0	0.8 ± 0.1	
DRS-20	20.0	0.5 ± 0.1	10.0	0.9 ± 0.1	
DRS-22	22.0	0.5 ± 0.1	11.0	0.9 ± 0.1	
DRS-25	25.0	0.5 ± 0.1	12.5	0.9 ± 0.1	25
DRS-28	28.0	0.5 ± 0.1	14.0	0.9 ± 0.1	
DRS-30	30.0	0.5 ± 0.1	15.0	1.00 ± 0.2	
DRS-35	35.0	0.5 ± 0.1	17.5	1.00 ± 0.2	
DRS-40	40.0	0.5 ± 0.1	20.0	1.00 ± 0.2	
DRS-50	50.0	0.5 ± 0.1	25.0	1.00 ± 0.2	
DRS-60	60.0	0.6 ± 0.1	30.0	1.20 ± 0.2	
DRS-70	70.0	0.6 ± 0.1	35.0	1.20 ± 0.2	
DRS-80	80.0	0.6 ± 0.1	40.0	1.20 ± 0.2	
DRS-90	90.0	0.6 ± 0.1	45.0	1.30 ± 0.2	
DRS-100	100.0	0.7 ± 0.1	50.0	1.30 ± 0.2	
DRS-120	120.0	0.7 ± 0.1	60.0	1.30 ± 0.2	
DRS-150	150.0	0.8 ± 0.1	75.0	1.60 ± 0.2	