

### Weather Protected Isolating Switch


#### WEATHER PROTECTED

The WP Series of Weatherprotected Isolating switches is a robust range of switches suitable for virtually any external application. Included in the range are single, double and triple pole switches from 20 to 80 Am-ps. The base mounted mechanism provides for easier termination and more wiring room. Switch dimensions are 165mm x 82mm with an overall height of 85mm

#### ISOLATING SWITCHES

Fixed Earth and Neutral connector bars with dual clamping screws per tunnel provide equal stripping lengths and secure clamping for all cables. Terminal bore size 5 x 6.6mm

A safety feature for mounting switches to metal structures is the insulating caps that cover base mounting screws to totally protect them from any live cables.



Products Available	Phase & Voltage	IP Rating
WP1-20	20A 250V Single pole surface switch. Terminals accommodate 16mm <sup>2</sup> cable.M Rating220.	56
WP1-35 WP1-63	36A/63A 250V Single pole Terminals accommodate 16mm <sup>2</sup> cable.M Rating220.	56
WP1-20A-16 WP1-35A-16 WP1-63A-25	Single phase 250V conduit: ϕ 25mm	56
WP2-20A-16 WP2-35A-16 WP2-63A-25	Double phase 440V conduit: ϕ 25mm	56
WP3-20A-16 WP3-35A-16 WP3-63A-25	Three phase 440V conduit: ϕ 25mm	56
WP3-55A-25 WP3-63A-25 WP3-80A-25	Three phase 440V conduit: ϕ 32mm	56
WP2-20	20A 440V Double pole Terminals accommodate 16mm <sup>2</sup> cable.M Rating180.	56
WP2-35	35A 440V Double pole Terminals accommodate 16mm <sup>2</sup> cable.M Rating180.	56
WP2-63	63A 440V Double pole Terminals accommodate 25mm <sup>2</sup> cable.M Rating160.	56
WP3-20	20A 440V Triple pole Terminals accommodate 16mm <sup>2</sup> cable.M Rating180.	56
WP3-35	35A 440V Triple pole Terminals accommodate 16mm <sup>2</sup> cable.M Rating180.	56
WP3-55	55A 440V Triple pole Terminals accommodate 16mm <sup>2</sup> cable.M Rating160.	56
WP3-55-32CE	55A 440V Triple pole. with 32mm conduit entry at each end. Terminals accommodate 25mm <sup>2</sup> cable.M Rating160.	56
WP3-63-32EC	63A 440V Triple pole. with 32mm conduit entry at each end. Terminals accommodate 25mm <sup>2</sup> cable.M Rating160.	56
WP3-80-32EC	80A 440V Triple pole. with 32mm conduit entry at each end. Terminals accommodate 25mm <sup>2</sup> cable.M Rating150.	56