

Full spiral/Half Spiral Energy Saving Lamps

SPECIFICATIONS

CE & ROHS, ISO9001

1. Voltage/Frequency: 110V-130V/220V-240V, 50/60Hz;

2. Power: 7W ~ 105W;

3. Base: E27 / E22 / E14 / E17 / E40 / B22;

4. Life: 5000~10000 hrs;

5. Color temperature: 2700k - 7000k;

6. Tube inside powder: Halogen / tri-color / mixed powder;

7. Packaging: Standard Export Carton.



YPZ7-HS



YPZ15-HS



YPZ55-HS



YPZ7-FS



YPZ11-FS



YPZ65-FS

Type	Voltage (V)	Watt (W)	Luminous Flux (lm)	Color temp (k)	Tubular (mm)	Size (mm)	Life (hrs)	Base
YPZ7-HS	110-130 220-240	7	420	2700 3200 4500 5000 6400 6500 7000	φ 9	105	5000-10000	E14 E17 E27 E22 B22 E40
YPZ9-HS		9	630		φ 9	110		
YPZ11-HS		11	660		φ 9	115		
YPZ13-HS		13	780		φ 9	120		
YPZ15-HS		15	900		φ 9	125		
YPZ20-HS		20	1100		φ 12	150		
YPZ23-HS		23	1265		φ 12	158		
YPZ26-HS		26	1460		φ 12	166		
YPZ45-HS		45	2700		φ 14/ φ 16	210		
YPZ55-HS		55	3300		φ 14/ φ 16	220		
YPZ65-HS		65	3900		φ 14/ φ 16	280		
YPZ85-HS		85	5400		φ 17	255		
YPZ105-HS		105	6800		φ 17	285		
YPZ9-FS	110-130 220-240	9	580	2700 3200 4500 5000 6400 6500 7000	φ 9	95	5000-10000	E14 E17 E27 E22 B22 E40
YPZ11-FS		11	710		φ 9	100		
YPZ13-FS		13	840		φ 9	105		
YPZ15-FS		15	980		φ 9	110		
YPZ18-FS		18	1200		φ 9	115		
YPZ20-FS		20	1300		φ 12	140		
YPZ22-FS		22	1450		φ 12	145		
YPZ26-FS		26	1700		φ 12	155		
YPZ45-FS		45	2900		φ 16	155		
YPZ55-FS		55	3500		φ 16	170		
YPZ65-FS		65	4200		φ 16	185		